

ACCESS 100 AC

2-way coaxial kit

- (DFS®) Dual Fiberglass Structure cone
High resistance (Power, climatic conditions, humidity...)
- Grilles new design
Profiled

- Butyl surround
Longlife
- Tilted tweeter on rotativ pod
Optimization of the sound stage



- ABS basket with 20% of fiberglass
Non magnetic, non resonant
- 25mm (1") voice coil (2 Kapton® layer)
High power handling

- 72mm magnet
High sentivity
- Integrated crossover (4.7 kHz)
Easy and quick installation

- Inverted dome tweeter
Accuracy, sound staging optimization

WHAT MAKES THE DIFFERENCE

- Cone DFS® (Dual fiberglass Structure)
(climatic and power) high resistance
- Compact basket
- Rotativ tweeter

TECHNICAL CHARACTERISTICS

Woofer: 4" (100mm)

Voice-coil diameter: 1" (25mm)

Voice-coil height: 0⁷/₁₆" (11mm)

Magnet: 2¹³/₁₆" (72mm)

Tweeter: Aluminum inverted dome

Crossover: (4,7Khz) 6dB/oct

Max. power: 80 Watts

Nom. power: 40 Watts RMS

Sensitivity (2.83V/1m): 87.2dB

Frequency response: 70Hz – 20kHz

Accessories: Supplied grilles

 **Performance**
CREATE YOUR SOUND

 **FOCAL**
THE SPIRIT OF SOUND