

ACCESS 130 AS

2-way component kit

- (DFS®) Dual Fiberglass Structure cone
High resistance (Power, climatic conditions, humidity...)
- Phase plug
Midrange control
- Grilles new design
Profiled

- Adjustable tweeter level
(3 positions : -3 / 0 / +3dBoct)
Soundstage positioning
- Air core inductors
Insensitive to parasite interferences



- ABS basket with 20% of fiberglass
Non magnetic, non resonant
- 25mm (1") voice coil (2 Kapton® layer)
High power handling

- 85mm magnet
High sensitivity

- Aluminum inverted dome tweeter
Accurate treble

CE QUI FAIT LA DIFFÉRENCE

- Cone DFS® (Dual fiberglass Structure)
(climatic and power) high resistance
- Tweeter level adjustment

TECHNICAL CHARACTERISTICS

Woofer: 5" (130mm)
Voice-coil diameter: 1" (25mm)
Voice-coil height: 0⁷/₁₆" (11mm)
Magnet: 3¹/₃" (85mm)
Tweeter: Aluminum inverted dome
Adjustable Tweeter level: 3 positions (-3/0/+3dB)

Crossover: 12dB/oct
Max. power: 100 Watts
Nom. power: 50 Watts RMS
Sensitivity (2.83V/1m): 90dB
Frequency response: 65Hz – 20kHz
Accessories: Supplied grilles

