



L7T82

Power Handling
350 Watts RMS / 700 Watts Max.

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	46 mm
Voice Coil Winding Height		22,5 mm
Max. Linear Excursion	Xmax	+/- 7,25 mm
Cone Area	Sd	269 cm ²
Moving Mass	Mms	119,7 g
DC Resistance	Re	2 x 1,9 Ohms
Resonance Frequency	Fs	45,4 Hz
Mechanical Q-Factor	Qms	8,52
Electrical Q-Factor	Qes	0,67
Total Q-Factor	Qts	0,63
Equivalent Air Volume	VAS	12,7 L
VC Inductance	Le	3,44 mH
Flux Density	B/L	13,05 N/A
Efficiency 1W/1m	SPL	84,8 dB

Dual Voice Coil
Subwoofer 20 cm

Recommended Enclosure

Ported Box	
Vented Volume:	34 L
Port Diameter:	115 mm
Port Area:	104 cm ²
Port Length:	48,6 cm

Deep Bass Box

Recommended Enclosure

Ported Box	
Vented Volume:	22,7 L
Port Diameter:	100 mm
Port Area:	78 cm ²
Port Length:	52 cm

Compact Box

Mechanical Components

- Steel Basket
- Polypropylene Cone
- Santoprene Surround
- Polypropylene Dustcap
- Poly Cotton Spider
- Y30 Magnet 37 oz (1.049 g)
- Magnet Size: Ø136 x 18 mm

Dimensions & Weight

External Diameter:	224 x 224 mm
Mounting Diameter:	188 x 188 mm
Mounting Depth:	70 mm
Shipping Weight:	4,2 kg

