



L7T102

Power Handling
500 Watts RMS / 1000 Watts Max.

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	56 mm
Voice Coil Winding Height		28,4 mm
Max. Linear Excursion	Xmax	+/- 9,2 mm
Cone Area	Sd	433 cm ²
Moving Mass	Mms	199,2 g
DC Resistance	Re	2 x 1,8 Ohms
Resonance Frequency	Fs	30,8 Hz
Mechanical Q-Factor	Qms	9,33
Electrical Q-Factor	Qes	0,56
Total Q-Factor	Qts	0,53
Equivalent Air Volume	VAS	44,6 L
VC Inductance	Le	5,63 mH
Flux Density	B/L	17,3 N/A
Efficiency 1W/1m	SPL	86 dB

Dual Voice Coil
Subwoofer 25 cm

Recommended Enclosure

Ported Box	
Vented Volume:	49,6 L
Port Diameter:	148 mm
Port Area:	170 cm ²
Port Length:	50,8 cm

Deep Bass Box

Recommended Enclosure

Ported Box	
Vented Volume:	35,4 L
Port Diameter:	130 mm
Port Area:	136 cm ²
Port Length:	50,8 cm

Compact Box

Mechanical Components

- Steel Basket
- Polypropylene Cone
- Santoprene Surround
- Polypropylene Dustcap
- Poly Cotton Spider
- Y30 Magnet 60 oz (1.701 g)
- Magnet Size: Ø157 x 21,5 mm

Dimensions & Weight

External Diameter:	272 x 272 mm
Mounting Diameter:	237 x 237 mm
Mounting Depth:	95 mm
Shipping Weight:	7,1 kg

