

KICKER®

L7T122

Power Handling
600 Watts RMS / 1200 Watts Max.

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	63 mm
Voice Coil Winding Height		30,5 mm
Max. Linear Excursion	Xmax	+/- 10,25 mm
Cone Area	Sd	645 cm ²
Moving Mass	Mms	291,7 g
DC Resistance	Re	2 x 1,9 Ohms
Resonance Frequency	Fs	26,3 Hz
Mechanical Q-Factor	Qms	8,76
Electrical Q-Factor	Qes	0,64
Total Q-Factor	Qts	0,59
Equivalent Air Volume	VAS	88,8 L
VC Inductance	Le	6,41 mH
Flux Density	B/L	15,88 N/A
Efficiency 1W/1m	SPL	86,5 dB

Dual Voice Coil
Subwoofer 30 cm

Recommended Enclosure

Ported Box	
Vented Volume:	63,7 L
Port Diameter:	175 mm
Port Area:	242 cm ²
Port Length:	52,1 cm

Deep Bass Box

Recommended Enclosure

Ported Box	
Vented Volume:	49,6 L
Port Diameter:	160 mm
Port Area:	203 cm ²
Port Length:	50,8 cm

Compact Box

Mechanical Components

- Steel Basket
- Polypropylene Cone
- Santoprene Surround
- Polypropylene Dustcap
- Poly Cotton Spider
- Y30 Magnet 68 oz (1.928 g)
- Magnet Size: Ø170 x 21,5 mm

Dimensions & Weight

External Diameter:	321 x 321 mm
Mounting Diameter:	281 x 281 mm
Mounting Depth:	105 mm
Shipping Weight:	0,0 kg

